

# Data Vision LCD Coding System

## Character LCM

For example:



1	Display Type	DV	Character LCM									
2	RoHS compliant											
3	Character font	Columns (V) x Lines (H)										
4	Series number											
5	Version No.											
6	LCD Mode	S	S1-Yellow Green,STN				W	FSTN				
			S2-Silver gray,STN				N	Twist Nematic				
7	Polarizer Mode	R	Reflective				F	Transflective				
		M	Transmissive				N	Negative				
8	View Direction	B	Bottom view (6H)				T	Top view (12H)				
9	Backlight	E	EL				L	LED		C	C.C.F.L.	
10	B/L color	A	Amber (EL, LED)				B	Blue-green (EL)		R	Red (LED)	
		W	White (EL, LED,CCFL)				Y	Yellow-green (EL, LED)				
11	Temp. Range		Normal Temperature				H	High Temperature				

## Graphic LCM

For example:



1	Display Type	DG	Graphic LCM									
2	RoHS compliant											
3	Graphic Resolution	Columns (X) x Rows (Y)										
4	Series No.											
5	LCD Mode	S	S1-Yellow Green, STN				W	FSTN				
			S2-Silver Gray, STN									
6	Polarizer Mode	R	Reflective				F	Transflective				
		N	Negative				M	Transmissive				
7	View Direction	B	Bottom view (6H)				T	Top view (12H)				
8	Backlight	E	EL				L	LED		C	C.C.F.L.	
9	B/L color	A	Amber (EL, LED)				B	Blue-green (EL)		R	Red (LED)	
		W	White (EL, LED,CCFL)				Y	Yellow-green (EL, LED)				
10	Temp. Range		Normal Temperature				H	High Temperature				
11	DC/DC											