Setting Pre-Emphasis Level for DS40MB200 Dual 4Gb/s Mux/Buffer

Introduction

The DS40MB200 is a dual 2:1 multiplexer and 1:2 fan-out repeater designed to support redundancy and extending copper backplane to data rates up to 4 Gb/s. With input equalization and output pre-emphasis, the DS40MB200 is capable of compensating attenuation distortion and reducing deterministic jitter caused by bandwidth-limited transmission lines. This application note outlines the methods to set the proper amount of equalization to achieve optimum jitter performance.

Each output driver of the DS40MB200 has pre-emphasis for compensating the transmission loss disparity of the trans-

National Semiconductor Application Note 1389 Tsun-Kit Chin. October 2005



mission medium that it is driving. *Figure 1* shows the preemphasized waveforms before and after a transmission medium. Whenever there is a transition of logic state, the driver sends the first data bit with its full amplitude. In anticipation of lower transmission loss from the transmission medium, the driver sends the subsequent data bits of the same logic state with reduced amplitude. Effectively, the driver conditions the output signal amplitude such that the lower and higher frequency pulses reach approximately the same amplitude at the receiving end of the transmission medium.



AN-1389

Introduction (Continued)

Pre-emphasis provides equalization on the driver side. The driver-side equalization minimizes deterministic jitter caused by amplitude disparity of the transmission line. The DS40MB200 provides 4 steps of user-selectable preemphasis ranging from 0, 3, 6 and 9 dB to handle different amount of transmission losses.

Each input stage of the DS40MB200 has a fixed equalizer. It provides boost to higher frequency signals that are attenuated by the transmission loss of the input board trace. The fixed equalizer is designed to equalize about 5 dB of transmission loss disparity from the input transmission line at 4 Gb/s. The input equalizer is capable of providing jitter reduction of about 30 ps caused by a 5 dB transmission loss. For higher transmission loss, driver pre-emphasis provides added equalization. With DS40MB200 on both ends of the transmission medium, they are capable to handle up to 14 dB of transmission loss and enable error free data transmission up to 4 Gb/s.

Transmission Loss

The proper amount of equalization is determined by the transmission loss of the interconnect elements within the operating frequency range. The spectrum of a bit stream depends on its data pattern. Two reference frequencies are commonly used. The frequency of an alternating-1-0 clock-like pattern is usually used as the upper frequency. Similarly, the frequency of the longest continuous 1's or continuous 0's repeating pattern is used as the lower frequency. The duration for the continuous 1's or continuous 0's is commonly called the Run Length. *Table 1* shows the lower and upper frequencies of some commonly used data patterns at which transmission losses are measured. *Table 2* shows the lower and upper frequencies of an 8b/10b bit stream at different data rates.

TABLE 1. Reference Frequencies versus Data Pattern
--

Data Pattern	Run Length	Lower Frequency	Upper Frequency
8b/10b Code	5 Bits	Bit Rate/(2*5)	Bit Rate/2
2 ⁷ -1	7 Bits	Bit Rate/(2*7)	Bit Rate/2
2 ¹⁰ -1	10 Bits	Bit Rate/(2*10)	Bit Rate/2

TABLE 2. Reference Frequencies with 8b/10b Code

Bit Rate	Run Length	Lower Frequency	Upper Frequency
1.25 Gb/s	5 Bits	125 MHz	625 MHz
2.5 Gb/s	5 Bits	250 MHz	1200 MHz
3.125 Gb/s	5 Bits	312.5 MHz	1562.5 MHz
4 Gb/s	5 Bits	400 MHz	2000 MHz

Methods To Determine The Proper Amount of Equalization

There are many ways to determine the loss of a transmission medium. If a network analyzer is available, it is the most accurate way to sweep the frequency response of the transmission medium. *Figure 2* shows the forward transmission characteristics of a 30-inch differential board trace measured by a 4-port network analyzer. Marker 1 (M1) is positioned at the lower frequency, and Marker 2 (M2) is positioned at the upper frequency. The difference in the two markers' positions indicates the transmission loss disparity between its lower and upper frequencies.

A differential Time-Domin Reflectometer (TDR) measures the step response of a transmission medium. The step response at the end of a transmission medium is commonly called the time-domain transmission (TDT) characteristics. There is third party software that converts the time-domain response to frequency-domain response, from which the transmission losses can be extracted.

In the absence of either a network analyzer or a TDR, a simple way is to send a periodic clock-like data pattern through the transmission medium and measure the transmission loss with an oscilloscope. An alternating-1-0 repeating pattern is used to measure the transmission loss at the upper reference frequency. An alternating-11111-00000 repeating pattern is used to measure the transmission loss at the lower reference frequency for an 8b/10b bit stream. The difference in the losses at the upper and lower reference frequencies is the attenuation distortion that we want to compensate by equalization.

The pre-emphasis level is chosen to compensate the attenuation distortion of the transmission medium. In the case of the 30-inch board trace running 8b/10b code at 4 Gb/s, the attenuation distortion from 400 MHz to 2000 MHz is 5.47 dB (see *Figure 2*). The driver is set to provide 6 dB preemphasis for properly equalizing the channel. Pre-emphasis of the DS40MB200 is selectable through 2-pin logic controls for 0, 3, 6 and 9 dB. *Figure 3* shows the eye diagram at the end of the 30-inch board trace with a (2^7 -1) pseudo-random bit stream running at 4 Gb/s without pre-emphasis. With 6 dB driver pre-emphasis, the data eye is wide open, providing ample of timing and amplitude margins. *Figure 4* shows the eye diagram with driver set to 6 dB of pre-emphasis.

An alternative method to select the proper amount of preemphasis is to try out all combinations of pre-emphasis



20156803

FIGURE 2. Transmission Loss of a 30-Inch FR4 Board Trace



FIGURE 3. Data Eye After 30-In FR4 Board Trace With **Pre-Emphasis Disabled**



FIGURE 4. Data Eye After 30-In FR4 Board Trace With 6 dB of Pre-Emphasis

Methods To Determine The Proper Amount of Equalization (Continued)

levels and pick the one that offers the lowest jitter and highest eye height performance. This method is by far the simplest approach without even knowing the loss of the transmission medium. With a try-and-error approach, it is important to visually recognize the effect of underequalization or over-equalization if too little or too much pre-emphasis is applied. Figure 5 shows the eye diagram of the same 30-inch FR4 board trace with driver set to 3 dB pre-emphasis, showing jitter degradation when underequalization. Figure 6 shows the eye diagram of overequalization when the amplitude of the higher frequency pulses is higher than that of the lower frequency pulses. Over-equalization usually introduces degradation in eye height.







FIGURE 6. Data Eye After 30-In FR4 Board Trace—Over Equalized

Complete Link With Transmit Pre-Emphasis And Receive Equalization

In a communication link where an equalizer is used at the receiver, the total amount of driver pre-emphasis and receiver equalization should be approximately equal to the attenuation distortion of the transmission medium. Figure 7 shows two DS40MB200 signal conditioners on both ends of a 20-inch backplane.

AN-1389

Complete Link With Transmit Pre-Emphasis And Receive Equalization (Continued)





In addition to skin loss and dielectric loss of FR4 board traces, backplane connector and the parasitic capacitance caused by plated-through-holes introduce added losses to the backplane. *Figure 8* shows the forward transmission characteristics of a 20-inch FR4 backplane with a high speed backplane connector on both ends. The attenuation distortion for this backplane is about 7.8 dB (see *Figure 8*). *Figure 9* shows the data eye after the backplane without any equalization. *Figure 10* shows the data eye opens up with the use of 3 dB driver pre-emphasis and about 5 dB receive equalization from the DS40MB200.



FIGURE 8. Transmission Loss of a 20-Inch FR4 Backplane With 2 High Speed Connectors



FIGURE 9. Data Eye After 20-In Backplane Without Equalization



FIGURE 10. Data Eye After 20-In Backplane with 3 dB Tx Pre-Emphasis and 5 dB Rx Equalization

Criteria for Equalization

In a typical communication sub-system, in addition to jitter caused by interconnects, there are also jitter components caused by crosstalk, supply noise and other switching noises. They are high frequency jitter components that are usually beyond the bandwidth of a receiver's phase-locked loop and cannot be filtered by the receiver's PLL. It is also costly to implement noise cancellation due to circuit complexity and variability of the noise profile. The goal of equalization is to minimize the residual deterministic jitter caused by interconnects and allow enough timing margin for the receiver to tolerate crosstalk and system noise.

The use of equalization achieves the following two goals:

- 1. The total jitter is within the range that a receiver can handle. Most receivers' PLL have a specification called Input Jitter Tolerance. It spells out the amount of jitter that the PLL can handle under a specific error rate performance.
- 2. The eye height is above the minimum input signal level that the receiver can handle. For DS40MB200, the minimum input level is 100 mV_{P-P} differential.

Figure 11 shows the eye diagram of an equalized 20-inch backplane in the presence of crosstalk. Due to the slow acquisition rate of an oscilloscope, an eye diagram taken by an oscilloscope is not adequate to quantify the total jitter introduced by a large number of data transitions. A common practice is to use the bathtub plot feature of a jitter instrument to predict the total jitter at a specific error rate. *Figure 12* shows a bathtub plot of the equalized 20-inch backplane, predicting total jitter of 98.4psp-p at an error rate of less than 10^{-12} . This amount of jitter corresponds to 0.394 UI (39.4% of one bit time) at 4 Gb/s. Most receivers' PLL can handle more than 0.5UI of jitter and minimum input signal level of 100 mV_{P-P}.



FIGURE 11. Data Eye After an Equalized 20-Inch Backplane in the Presence Of Crosstalk



FIGURE 12. Bathtub Plot Showing Prediction of Eye Opening at Various Error Rates

Conclusion

DS40MB200 provides user-selectable transmit preemphasis and fixed receive equalization that cover a wide range of transmission loss from FR4 board trace, backplane or cables. The DS40MB200 extends the reach and speed of copper transmission media for data rates up to 4 Gb/s.

Reference

Datasheet of DS40MB200 Dual 4 Gb/s 1:2 Mux/Buffer with Input Equalization and Output Pre-emphasis, National Semiconductor Corp., www.national.com

4-port network analyzer and Time Domain Reflectometer, Agilent Technology, www.agilent.com

TDR software that extracts transmission loss from TDR, TDA Systems, www.tdasystems.com

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

For the most current product information visit us at www.national.com.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
- A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

BANNED SUBSTANCE COMPLIANCE

National Semiconductor manufactures products and uses packing materials that meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no "Banned Substances" as defined in CSP-9-111S2.

Leadfree products are RoHS compliant.

National Semiconductor Americas Customer Support Center Email: new.feedback@nsc.com Tel: 1-800-272-9959

National Semiconductor Europe Customer Support Center Fax: +49 (0) 180-530 85 86 Email: europe.support@nsc.com Deutsch Tel: +49 (0) 69 9508 6208 English Tel: +44 (0) 870 24 0 2171 Français Tel: +33 (0) 1 41 91 8790 National Semiconductor Asia Pacific Customer Support Center Email: ap.support@nsc.com National Semiconductor Japan Customer Support Center Fax: 81-3-5639-7507 Email: jpn.feedback@nsc.com Tel: 81-3-5639-7560

www.national.com

AN-1389